



## KÖSTER KB-FIX 1

### Fast setting cement for swift installations

#### Features

Extremely fast setting mortar (sets after approx. 1 minute) for swift installations. Waterproof and weatherproof.

#### Technical Data

Starts to set after approx. 60 seconds (20°C)  
Application of next layer after approx. 2 hours

#### Fields of Application

KÖSTER KB-Fix 1 is intended for swift filling of holes and cracks in plaster and masonry, for anchoring wall anchors, anchor fittings, brackets of roof gutters and down pipes, handrails, grates, radiators as well as for swift repairs at home, for sealing pipe penetrations. KÖSTER KB-Fix 1 is suitable for both inside and outside use.

#### Substrate

Remove loose particles from plaster and masonry and prewet holes or cracks with, install insert parts.

#### Application

Mix 3 parts of KÖSTER KB-Fix 1 with 1 part of water into a stiff, viscous mortar. When doing sealing work or when filling larger cavities, press the mortar into place using a board or trowel until it has set (don't prepare too much material).

In cold weather, mix KÖSTER KB-Fix 1 with warm water (approx. 20°C). KÖSTER KB-Fix 1 can be modified to give a slower reaction time and a lower compressive strength by adding washed sand and Portland cement (always carry out tests before installation).

#### Consumption

Approx. 1.8 kg/l void

#### Cleaning

Clean tools immediately after use with water.

#### Packaging

C 511 015 15 kg bucket

#### Storage

Store the material in a dry environment. In originally sealed packages, the material can be stored for a minimum of 6 months.

#### Safety

Wear protective gloves and goggles when processing the material.

#### Related products

KÖSTER KB-FIX 5 Prod. code C 515 015  
KÖSTER Spatula Prod. code X 987 001

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.